W-C-C 25°

Photometric Report





e-mail: service@glp.de Internet: http://www.glp.de







Impression 90 WCC 25° – Photometric Report

GLP R&D Center Germany, 15.07.2010

Manufacturer: GLP German Light Products GmbH, Im Stöckmädle 13,

76307 Karlsbad, Germany

Product: Impression 90 WCC 25°

Light Source:

Model: Philips Lumileds Luxeon K2 LED

Configuration: 60 x cold white, 30 x warm white LED in WCC array configuration

Rated Service Lifetime: 50000 h

Power Supply:

Power supply: Electronic, built in

Power Factor: 0.994

Test conditions:

AC supply: U = 230 V AC / f = 50 Hz

Lens Option: 25°
Frost Filter Option: no
Room Temp.: 25℃
Position: horizontal
Symmetry: rational
Efficiency factor: 100%

Photometric Procedure:

Date: 15.07.2010

Goniometer Model: LMT GO-DS 2000 automated Goniometer

Measurement Method: DIN EN 13032-1 / C-Layer Measurement dC15% dG0,5°

Throw distance: 14,56m

Data File Format: according to ANSI/IESNA LM-63-02

File Name: Impression 90 WCC 25°.ies







Output: Electric Variable:

Total: $\gamma 90^{\circ} = 7359$ lumens Power Consumption: P = 345 W

 $\gamma 0^{\circ} = 5026 \text{ cd/klm}$ Current Draw: I = 1,5 A

Luminaire Type: Multiple-lamp Far-field luminaire

Luminaire efficacy: 21.3 lm/W Intended throw: >= 3m

Ambient Temperature Limits: 0°C - 45°C

Dimension (L x W x H): 234 x 340 x 320 mm

Dimension Lens (H x Ø): 30 x 225 mm **Weight:** 7.5 Kg


Approvals: Din EN ISO/IEC 17025:2005, EN 60598-1, EN 60598-2-17,

EN 55 015, EN 55 103, EN 61 000-3 ANSI/UL 1573, CSA C22.2 No. 166

Disclaimer: The information in this document is provided in connection with the described product only. In no event shall GLP be liable for any direct, indirect, consequential, punitive, special or incidental damages (including, without limitation, damages for loss of profits, business interruption, or loss of information) arising out of the use or inability to use this document or its content, even if GLP has been advised of the possibility of such damages. GLP makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. GLP does not make any commitment to update the information contained herein.

Illuminance distribution diagram

Full on





Polarcurve diagrams:

Full on

